

Dell UltraSharp U2721DE (DELL-U2721DE)
Dell UltraSharp U2721DE - LED monitor - 27" (27"viewable) - 2560 x 1440 QHD - IPS - 350 cd/m²
- 1000:1 - 5 ms - HDMI ,2xDisplayPort - with 3 years Advanced Exchange Service



Get a stable,wired connection to your network and peripherals on this sleek 27"QHD hub monitor with RJ45,USB-C and a host of other ports.

Key Selling Points

In-plane switching technology
Anti-glare treatment of the front polarizer (3H) hard coating
Response time: 8 ms for normal mode,5 ms for fast mode

Main Specifications

Product Description	Dell UltraSharp U2721DE - LED monitor - 27"
Device Type	LED-backlit LCD monitor - 27"
Features	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.233 mm
Brightness	350 cd/m²
Contrast Ratio	1000:1
Response Time	8 ms (normal);5 ms (fast)
Colour Support	16.7 million colours
Input Connectors	HDMI ,2xDisplayPort
Display Position Adjustments	Height,pivot (rotation),swivel,tilt
Screen Coating	Anti-glare,3H Hard Coating
Dimensions (WxDxH) - with stand	61.22 cm x 18 cm x 39.02 cm
Environmental Standards	TCO Certified Displays 8,ENERGY STAR Qualified
Compliant Standards	RoHS,NFPA 99,BFR-free,DisplayPort 1.4,HDCP 1.4,PVC-free
Bundled Services	3 years Advanced Exchange Service

Extended Specification

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	USB 3.0 hub
Panel Type	IPS

Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.233 mm
Pixel Per Inch	109
Brightness	350 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	8 ms (normal); 5 ms (fast)
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	99% sRGB colour gamut, 99% Rec 709 colour gamut, 85% DCI-P3
Dimensions (WxDxH)	61.22 cm x 18 cm x 39.02 cm - with stand

Connectivity

Interfaces	DisplayPort (DisplayPort 1.4 mode) HDMI (HDCP) USB-C 3.1 Gen 1 upstream/DisplayPort with Power Delivery (power up to 65W) DisplayPort output (MST) 2 x USB 3.0 downstream 2 x USB 3.0 downstream with Battery Charging 1.2 Audio line-out (mini-jack) Network (RJ-45)
------------	--

Mechanical

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	80
Height Adjustment	130 mm
VESA Mounting Interface	100 x 100 mm

Miscellaneous

Features	Security lock slot (cable lock sold separately), VESA interface support, anti-theft stand lock slot
Cables Included	1 x DisplayPort cable - DisplayPort to DisplayPort 1 x USB-C to USB-C cable
Compliant Standards	RoHS, NFPA 99, BFR-free, DisplayPort 1.4, HDCP 1.4, PVC-free

Power

Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	33.2 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption Sleep	0.3 Watt

Dimensions &Weight

Dimensions &Weight Details	With stand - width: 61.22 cm - depth: 18 cm - height: 39.02 cm Without stand - width: 61.22 cm - depth: 3.9 cm - height: 35.5 cm - weight: 4.19 kg
----------------------------	---

Dimensions &Weight
(Shipping)

Shipping Weight	8.72 kg
-----------------	---------

Environmental Standards

TCO Certified	TCO Certified Displays 8
ENERGY STAR Certified	Yes

Manufacturer Warranty

Bundled Services	3 years Advanced Exchange Service
------------------	-----------------------------------

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)

*Tech Data is not responsible for errors in the documentation of products.