



WYSE 3040 THIN CLIENT

Quad-core performance on a budget

The Wyse 3040 is a highly affordable thin client delivering strong performance and great value for task and basic productivity users in virtual desktop environments. Based on an Intel quad-core processor, this thin client offers enhanced performance for light multi-tasking and supports dual monitors at 2560x1600 @ 60Hz. The Wyse 3040 features hardened, optimized Wyse ThinLinux as well as virus-resistant Wyse ThinOS.

Extremely compact and energy efficient, the Wyse 3040 runs on less than 5 watts and offers many years of efficient, secure and highperformance service.

Flexible connectivity

The Wyse 3040 can connect to a variety of virtual desktop brokers including Citrix XenDesktop, VMware Horizon and Microsoft RDS right out of the box. It offers excellent multimedia capabilities and essential protocol and peripheral support including optional PCoIP that enables connection to Amazon WorkSpaces (AWS) and a wide range of connectivity options including two DisplayPort interfaces, four USB ports, one of which is USB3.0, as well as wired and wireless network connections.

Easy to manage, highly scalable

The Wyse 3040 thin client is highly manageable through Wyse Device Manager (WDM) and Wyse Cloud Client Manager (CCM). Administration easily scales from just a few to tens of thousands of thin clients.

With Wyse thin clients, customers get a complete services portfolio including Deployment Services, ProSupport and Accidental Damage service, and with Dell business partners, end-to-end support throughout the product lifecycle.

Learn More: Visit www.dell.com/wyse

WYSE 3040 THIN CLIENT SPECIFICATIONS

OPERATING SYSTEM	Wyse ThinOS (with optional PCoIP support) Wyse ThinLinux
CPU	Intel Atom x5-Z8350 (Quad Core 1.44 GHz)
MEMORY	2GB DDR3L 1600MHz, solder down
STORAGE	8GB(for ThinOS configurations) /16GB (for ThinLinux configurations) eMMC flash chip, solder down
I/O PERIPHERAL SUPPORT	3 x USB 2.0 1 x USB 3.0 1 x audio-mic combo jack 2 X DisplayPort 1 x 1Gb/s RJ45 1 X Dual Band 802.11a/b/g/n/ac wireless
SECURITY	Built-in Kensington Security Slot (cable sold separately)
NETWORKING	Dual band 802.11 a/b/g/n/ac wireless, 10Mb/100Mb/1Gb Copper RJ45 (Wired Ethernet)
MULTIMEDIA	Audio-mic combo jack Integrated speakers
DISPLAY	Dual display port support (2560x1600 @ 60Hz)
POWER CONSUMPTION	15 watts max
POWER INPUT VOLTAGE RANGE	5V, 3A, 15W
DIMENSIONS	Height 101.6 mm (without stand) Width 27.94 mm Depth 101.6 mm
WEIGHT	0.24 kg (0.53 lbs)
TEMPERATURE RANGE	Operating: 32°to 104°F (10°to 40°C) Storage: 14°to 140°F (-10°to 60°C)
HUMIDITY	20% to 80% condensing. 10% to 95% non-condensing
WARRANTY	Three-year limited hardware warranty with optional ProSupport
SUPPORT AND DEPLOYMENT	Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service.