## Dell UltraSharp U2719D(DELL-U2719D)

Dell UltraSharp U2719D - LED monitor - 27" (27" viewable) - 2560 x 1440 QHD @ 60 Hz - IPS - 350 cd/m<sup>2</sup> - 1000:1 - 5 ms - HDMI, DisplayPort - with 3-Years Advanced Exchange Service and Premium Panel Guarantee - for Latitude 7400 2-in-1; XPS 13 9380, 15 9570



See fine details and true-to-life color on this 27"QHD monitor in an innovative, stylishly thin design.

## Key Selling Points

Impressive color precision &accuracy Wide viewing angles Brilliant screen resolution Ergonomic features

## Main Specifications

Product Description	Dell UltraSharp U2719D - LED monitor - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class A
Energy Consumption per Year	38 kWh
Power Consumption (On mode)	26 W
Features	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.233 mm
Brightness	350 cd/m <sup>2</sup>
Contrast Ratio	1000: 1
Response Time	8 ms (normal);5 ms (fast)
Colour Support	16.7 million colours
Input Connectors	HDMI, DisplayPort
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare,3H Hard Coating
Dimensions (WxDxH) - with stand	61.2 cm x 18 cm x 39 cm
Weight	8.52 kg
Localisation	United States
Environmental Standards	TCO Certified Displays 8, ENERGY STAR Qualified
Compliant Standards	RoHS, BFR-free, HDCP 1.4, PVC-free
Bundled Services	3-Years Advanced Exchange Service and Premium Panel Guarantee
Designed For	Latitude 7400 2-in-1; XPS 13 9380,15 9570

Extended Specification

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class A
Energy Consumption per Year	38 kWh
Diagonal Size	27"
Viewable Size	27"
Built-in Devices	USB 3.0 hub
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.233 mm
Pixel Per Inch	109
Brightness	350 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	8 ms (normal);5 ms (fast)
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare,3H Hard Coating
Backlight Technology	LED backlight
Features	Mercury free,99.9% sRGB colour gamut,arsenic-free glass,Dell Easy Arrange,99% Rec 709 colour gamut,85% DCI-P3
Dimensions (WxDxH)	61.2 cm x 18 cm x 39 cm - with stand
Weight	8.52 kg
Connectivity	
Interfaces	DisplayPort (HDCP) HDMI (HDCP) DisplayPort output (MST) 2 x USB 3.0 downstream 2 x USB 3.0 downstream with Battery Charging 1.2 USB 3.0 upstream Audio line-out (mini-jack)
Mechanical	
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	80
Height Adjustment	130 mm
VESA Mounting Interface	100 x 100 mm
Miscellaneous	
Features	Security lock slot (cable lock sold separately),VESA interface support,anti-theft stand lock slot
Cables Included	1 x DisplayPort cable 1 x SuperSpeed USB cable
Compliant Standards	RoHS,BFR-free,HDCP 1.4,PVC-free
Localisation	United States
Security Slot Type	Kensington security slot
Security Slot Type	

Power

Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption (On mode)	26 W
Power Consumption Operational	30 Watt
Power Consumption (Off Mode)	0.3 Watt
On / Off Switch	No
Dimensions &Weight	
Dimensions & Weight Details	With stand - width:61.2 cm - depth:18 cm - height:39 cm - weight:8.52 kg Without stand - width:61.22 cm - depth:3.9 cm - height:35.5 cm - weight:3.92 kg
Environmental Standards	
TCO Certified	TCO Certified Displays 8
ENERGY STAR Certified	Yes
Manufacturer Warranty	
Bundled Services	3-Years Advanced Exchange Service and Premium Panel Guarantee
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)
Compatibility Information	
Designed For	Dell Latitude 7400 2-in-1 Dell XPS 13 9380,15 9570

\*Tech Data is not responsible for errors in the documentation of products.