Dell S2721H(DELL-S2721H)

Dell S2721H - LED monitor - 27" (27" viewable) - 1920 x 1080 Full HD (1080p) @ 75 Hz - IPS - 300 cd/m² - 1000:1 - 4 ms - 2xHDMI - speakers - with 3 years Advanced Exchange Basic Warranty



This monitor is beautifully designed to sit easily into any space ready for your everyday lifestyle.

Main Specifications

Product Description	Dell S2721H - LED monitor - Full HD (1080p) - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class D
Energy Consumption per Year	27 kWh
Power Consumption (On mode)	16.8 W
Adaptive-Sync Technology	AMD FreeSync
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch	0.3114 mm
Brightness	300 cd/m ²
Contrast Ratio	1000: 1
Response Time	4 ms (grey-to-grey extreme)
Colour Support	16.7 million colours
Input Connectors	2xHDMI
Display Position Adjustments	Tilt
Screen Coating	Anti-glare,3H Hard Coating
Voltage	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH) - with stand	60.99 cm x 18.68 cm x 45.33 cm
Environmental Standards	TCO Certified Displays 8, ENERGY STAR Qualified
Compliant Standards	RoHS, HDCP 1.4
Bundled Services	3 years Advanced Exchange Basic Warranty

Extended Specification

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class D
Energy Consumption per Year	27 kWh
Diagonal Size	27"
Viewable Size	27"

Adaptive-Sync Technology	AMD FreeSync
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch	0.3114 mm
Pixel Per Inch	81.59
Brightness	300 cd/m ²
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Response Time	4 ms (grey-to-grey extreme)
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare,3H Hard Coating
Backlight Technology	LED backlight
Features	LED edgelight system,72% NTSC (CIE 1931) colour gamut,Flicker Free technology,BFR/PVC-free,Mercury free,arsenic-free glass,Dell Easy Arrange,Dell ComfortView,Low Blue Light technology,3-sided bezeless
Dimensions (WxDxH)	60.99 cm x 18.68 cm x 45.33 cm - with stand
Audio	
Туре	Speakers - stereo
Output Power / Channel	3 Watt
Connectivity	
Connectivity	
Interfaces	2 x HDMI (HDCP 1.4) Audio line-out
Interfaces	
Interfaces Mechanical	Audio line-out
Interfaces Mechanical Display Position Adjustments	Audio line-out Tilt
Interfaces Mechanical Display Position Adjustments Tilt Angle	Audio line-out Tilt -5/+21
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface	Audio line-out Tilt -5/+21
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface Miscellaneous	Audio line-out Tilt -5/+21 100 x 100 mm
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface Miscellaneous Features	Audio line-out Tilt -5/+21 100 x 100 mm Integrated cable management,VESA interface support,HDCP Compliant
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface Miscellaneous Features Included Accessories	Audio line-out Tilt -5/+21 100 x 100 mm Integrated cable management,VESA interface support,HDCP Compliant Stand,VESA cover,stand base
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface Miscellaneous Features Included Accessories Cables Included	Audio line-out Tilt -5/+21 100 x 100 mm Integrated cable management,VESA interface support,HDCP Compliant Stand,VESA cover,stand base 1 x HDMI cable
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface Miscellaneous Features Included Accessories Cables Included Compliant Standards	Audio line-out Tilt -5/+21 100 x 100 mm Integrated cable management,VESA interface support,HDCP Compliant Stand,VESA cover,stand base 1 x HDMI cable
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface Miscellaneous Features Included Accessories Cables Included Compliant Standards	Audio line-out Tilt -5/+21 100 x 100 mm Integrated cable management,VESA interface support,HDCP Compliant Stand,VESA cover,stand base 1 x HDMI cable RoHS,HDCP 1.4
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface Wiscellaneous Features Included Accessories Cables Included Compliant Standards Power	Audio line-out Tilt -5/+21 100 x 100 mm Integrated cable management,VESA interface support,HDCP Compliant Stand,VESA cover,stand base 1 x HDMI cable RoHS,HDCP 1.4 AC 120/230 V (50/60 Hz)
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface Wiscellaneous Features Included Accessories Cables Included Compliant Standards Power Input Voltage Power Consumption (On mode) Power Consumption SDR (On	Audio line-out Tilt -5/+21 100 x 100 mm Integrated cable management,VESA interface support,HDCP Compliant Stand,VESA cover,stand base 1 x HDMI cable RoHS,HDCP 1.4 AC 120/230 V (50/60 Hz) 16.8 W
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface VESA Mounting Interface Viscellaneous Features Features Included Accessories Cables Included Compliant Standards Power Input Voltage Power Consumption (On mode)	Audio line-out Tilt -5/+21 100 x 100 mm Integrated cable management,VESA interface support,HDCP Compliant Stand,VESA cover,stand base 1 x HDMI cable RoHS,HDCP 1.4 AC 120/230 V (50/60 Hz) 16.8 W 16.8 kWh/1000h
Interfaces Mechanical Display Position Adjustments Tilt Angle VESA Mounting Interface Wiscellaneous Features Features Included Accessories Cables Included Compliant Standards Power Power	Audio line-out Tilt -5/+21 100 x 100 mm Integrated cable management,VESA interface support,HDCP Compliant Stand,VESA cover,stand base 1 x HDMI cable RoHS,HDCP 1.4 AC 120/230 V (50/60 Hz) 16.8 W 16.8 kWh/1000h 21 Watt

Software / System Requirements	
Included Software	Dell Display Manager
Dimensions &Weight	
Dimensions &Weight Details	With stand - width:60.99 cm - depth:18.68 cm - height:45.33 cm Without stand - width:60.99 cm - depth:5.4 cm - height:36.36 cm - weight:4.4 kg
Dimensions &Weight (Shipping)	
Shipping Weight	7.7 kg
Environmental Standards	
TCO Certified	TCO Certified Displays 8
ENERGY STAR Certified	Yes
Manufacturer Warranty	
Bundled Services	3 years Advanced Exchange Basic Warranty
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)

What's in the box

Dell S2721H HDMI cable Stand,VESA cover,stand base Software

*Tech Data is not responsible for errors in the documentation of products.