Dell SE2422H(DELL-SE2422H)
Dell SE2422H - LED monitor - 24" (23.8" viewable) - 1920 x 1080 Full HD (1080p) @ 75 Hz - VA - 250 cd/m² - 3000:1 - 5 ms - HDMI,VGA



Enjoy the view on this slim-bezel Full HD display featuring a powerful processor. Enjoy fast response times and 75Hz refresh rate for leisure gaming.

Key Selling Points

Anti-glare with 3H hardness Advanced resolution Fast response times Incredible contrast ratio LED edge-light system AMD FreeSync technology Flicker-free technology VESA mounting interface

Main Specifications

| Product Description | Dell SE2422H - LED monitor - Full HD (1080p) - 24" |
|---------------------------------|--|
| Device Type | LED-backlit LCD monitor - 24" |
| Energy Class | Class E |
| Power Consumption (On mode) | 15.7 W |
| Adaptive-Sync Technology | AMD FreeSync |
| Panel Type | VA |
| Aspect Ratio | 16:9 |
| Native Resolution | Full HD (1080p) 1920 x 1080 (VGA: 60 Hz, HDMI: 75 Hz) |
| Pixel Pitch | 0.2745 mm |
| Brightness | 250 cd/m ² |
| Contrast Ratio | 3000:1 |
| Response Time | 12 ms (grey-to-grey normal); 8 ms (grey-to-grey fast); 5 ms (grey-to-grey extreme) |
| Colour Support | 16.7 million colours |
| Input Connectors | HDMI,VGA |
| Display Position Adjustments | Tilt |
| Screen Coating | Anti-glare,3H Hard Coating |
| Voltage | AC 100/240 V (50/60 Hz) |
| Dimensions (WxDxH) - with stand | 55.264 cm x 17.881 cm x 42.025 cm |
| Weight | 3.51 kg |
| Environmental Standards | TCO Certified Displays 8 |
| Compliant Standards | RoHS,BFR-free,HDCP 1.4,PVC-free,TÜV safety certification |
| Manufacturer Warranty | 3-year warranty |

Extended Specification

General

| Display Type | LED-backlit LCD monitor / TFT active matrix |
|--------------------------|---|
| Energy Class | Class E |
| Diagonal Size | 24" |
| Viewable Size | 23.8" |
| Adaptive-Sync Technology | AMD FreeSync |
| Panel Type | VA |
| Aspect Ratio | 16:9 |
| Native Resolution | Full HD (1080p) 1920 x 1080 (VGA:60 Hz,HDMI:75 Hz) |
| Pixel Pitch | 0.2745 mm |
| Pixel Per Inch | 92.56 |
| Brightness | 250 cd/m ² |
| Contrast Ratio | 3000:1 |
| Colour Support | 16.7 million colours |
| Response Time | 12 ms (grey-to-grey normal); 8 ms (grey-to-grey fast); 5 ms (grey-to-grey extreme) |
| Vertical Refresh Rate | 48 - 75 Hz |
| Horizontal Refresh Rate | 30 - 83 kHz |
| Horizontal Viewing Angle | 178 |
| Vertical Viewing Angle | 178 |
| Screen Coating | Anti-glare,3H Hard Coating |
| Backlight Technology | LED backlight |
| Features | 72% NTSC (CIE 1931) colour gamut, Flicker Free technology, slim bezel design, Mercury free, arsenic-free glass, Dell Easy Arrange, Dell Comfort View, Low Blue Light technology |
| Dimensions (WxDxH) | 55.264 cm x 17.881 cm x 42.025 cm - with stand |
| Weight | 3.51 kg |
| | |

Connectivity

Interfaces HDMI (HDCP 1.4) VGA

Mechanical

Display Position Adjustments Tilt

Tilt Angle -5/+21

VESA Mounting Interface 100 x 100 mm

Miscellaneous

Features Security lock slot (cable lock sold separately), VESA interface support

Cables Included 1 x HDMI cable

Compliant Standards RoHS,BFR-free,HDCP 1.4,PVC-free,TÜV safety certification

Security Slot Type Kensington security slot

Power

Input Voltage AC 100/240 V (50/60 Hz)

Power Consumption (On mode) 15.7 W

Power Consumption SDR (On

mode)

15.7 kWh/1000h

Power Consumption (Typical) 15.7 Watt

| Power Consumption (Max) | 24 Watt |
|-----------------------------------|---|
| Power Consumption Stand by | 0.3 Watt |
| Power Consumption (Off Mode) | 0.3 Watt |
| Software / System Requirements | |
| Included Software | Dell Display Manager |
| Dimensions &Weight | |
| | With stand - width: 55.264 cm - depth: 17.881 cm - height: 42.025 cm - weight: 3.51 |
| Dimensions &Weight Details | kg Without stand - width: 55.264 cm - depth: 4.969 cm - height: 33.161 cm - weight: 3.18 kg |
| Dimensions &Weight (Shipping) | |
| Shipping Weight | 5.23 kg |
| Environmental Standards | |
| TCO Certified | TCO Certified Displays 8 |
| Manufacturer Warranty | |
| Service &Support | Advanced Exchange Service - 3 years |
| Environmental Parameters | |
| Min Operating Temperature | 0 °C |
| Max Operating Temperature | 40 °C |
| Humidity Range Operating | 20 - 90% |

What's in the box

Dell SE2422H HDMI cable Software

 $[\]ensuremath{^{\star}}\mbox{Tech}$ Data is not responsible for errors in the documentation of products.