

Zyxel GS1200-8HP v2(GS1200-8HPV2-EU0101F)

Zyxel GS1200-8HP v2 - Switch - Managed - 4 x 10/100/1000 + 4 x 10/100/1000 (PoE+) - desktop - PoE+ (60 W)



Main Specifications

Product Description	Zyxel GS1200-8HP v2 - switch - 8 ports - Managed
Device Type	Switch - 8 ports - Managed
Subtype	Gigabit Ethernet
Ports	4 x 10/100/1000 + 4 x 10/100/1000 (PoE+)
Power Over Ethernet (PoE)	PoE+
PoE Budget	60 W
Performance	Switching capacity: 16 Gbps
Capacity	LAG groups: 2 Multicast groups: 128
MAC Address Table Size	4K entries
Jumbo Frame Support	9KB
Routing Protocol	IGMPv2, IGMP, IGMPv3
Remote Management Protocol	HTTP
Features	Flow control, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, Broadcast Storm Control, firmware upgradable, QoS, DHCP client, loop prevention, 192KB packet buffer, CoS, administrator's password, Link Aggregation, EEE, WRR, loopback detection, VLAN Tagging, port-based QoS
Compliant Standards	IEEE 802.3u, IEEE 802.3z, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at, IEEE 802.3az
Dimensions (WxDxH)	24 cm x 10.5 cm x 2.6 cm
Weight	584 g

Extended Specification

General

Device Type	Switch - 8 ports - Managed
Enclosure Type	Desktop
Subtype	Gigabit Ethernet
Ports	4 x 10/100/1000 + 4 x 10/100/1000 (PoE+)
Power Over Ethernet (PoE)	PoE+
PoE Budget	60 W
Performance	Switching capacity: 16 Gbps

Capacity	LAG groups: 2 Multicast groups: 128
MAC Address Table Size	4K entries
Jumbo Frame Support	9KB
Routing Protocol	IGMPv2, IGMP, IGMPv3
Remote Management Protocol	HTTP
Features	Flow control, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, Broadcast Storm Control, firmware upgradable, QoS, DHCP client, loop prevention, 192KB packet buffer, CoS, administrator's password, Link Aggregation, EEE, WRR, loopback detection, VLAN Tagging, port-based QoS
Compliant Standards	IEEE 802.3u, IEEE 802.3z, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at, IEEE 802.3az
Status Indicators	Port status, power, PoE

Expansion / Connectivity

Interfaces	4 x 1000Base-TX RJ-45 PoE+ - 30 W 4 x 1000Base-TX RJ-45
------------	---

Miscellaneous

Included Accessories	Rubber feet
Compliant Standards	EMC, FCC, RoHS, BSMI Class B, LVD

Power

Power Device	External power adapter
Power Provided	55 V - 1.3 A
Power Consumption Operational	72 Watt

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)
Min Storage Temperature	-40 °C
Max Storage Temperature	70 °C
Humidity Range Storage	10 - 90% (non-condensing)

Dimensions & Weight

Width	24 cm
Depth	10.5 cm
Height	2.6 cm
Weight	584 g

Dimensions & Weight (Shipping)

Shipping Width	25.6 cm
Shipping Depth	13.2 cm
Shipping Height	7.8 cm
Shipping Weight	1.153 kg

What's in the box

Zyxel GS1200-8HP v2
External power adapter, rubber feet

*TD SYNEX is not responsible for errors in the documentation of products.