











MINT+

- 700VA/1000VA/1200VA/1500VA line interactive UPS
- Built-in super smart charger, shorten 50% of charging time
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- · Auto restart while AC is recovering
- Simulated sine wave output
- Off-mode charging
- Cold start function
- USB-HID communication port and RJ-11/RJ-45 protection
- 5V USB charger port for modible devices
- LCD panels for selections & real-time UPS status
- Easy replaceable & hot-swappable battery
- NEXTVision shutdown software suite
- 3 years NEXT Onsite warranty

Mint+Line Interactive UPS Selection Guide

MODEL	Mint+ 700	Mint+ 1000	Mint+ 1200	Mint+ 1500
CAPACITY	700 VA / 420 W	1000 VA / 600 W	1200 VA / 720 W	1500 VA / 900 W
INPUT				
Voltage	220/230/240 VAC			
Voltage Range	170 - 280 VAC			
Frequency Range	60/50 Hz (auto sensing)			
ОUТРUТ				
Output Voltage	220/230/240 VAC			
AC Voltage Regulation (Batt. Mode)	±10%			
Frequency Range (Batt. Mode)	60 Hz or 50 Hz ±1 Hz			
Transfer Time	Typical 2-6 ms, 10ms max.			
Waveform (Batt. Mode)	Simulated Sinewave			
BATTERY				
Battery Type & Number	12 V / 9 Ah x 1	12 V / 9 Ah x 1	12 V / 9 Ah x 2	12 V / 9 Ah x 2
Typical Recharge Time	4-6 hours recover to 90% capacity			
PROTECTION				
Full Protection	Overload, discharge, and overcharge protection			
INDICATORS				
LCD Display	AC Mode, Battery Mode, Lo	oad Level, Battery Level, Input	Voltage, Output Voltage, Ove	rload, Fault, and Low Battery
ALARM				
Battery Mode	Sounding every 10 seconds			
Low Battery	Sounding every second			
Overload	Sounding every 0.5 second			
Battery Replacement Alarm	Sounding every 2 seconds			
Fault	Continuously sounding			
			sly sounding	
PHYSICAL			sly sounding	
PHYSICAL Dimension, D x W x H (mm)	288 x 99 x 280	288 x 99 x 280		99 x 280
	288 x 99 x 280 7.9	288 x 99 x 280 8.5		99 x 280 13.1
Dimension, D x W x H (mm)			410 x 9	
Dimension, D x W x H (mm) Net Weight (kgs)		8.5	410 x 9	
Dimension, D x W x H (mm) Net Weight (kgs) ENVIRONMENT		8.5 0-90 % RH @ 0- 40	410 x 9 11.8	
Dimension, D x W x H (mm) Net Weight (kgs) ENVIRONMENT Humidity		8.5 0-90 % RH @ 0- 40	410 x s 11.8 °C (non-condensing)	
Dimension, D x W x H (mm) Net Weight (kgs) ENVIRONMENT Humidity Noise Level	7.9	8.5 0-90 % RH @ 0- 40	410 x s 11.8 °C (non-condensing) an 40dB	13.1
Dimension, D x W x H (mm) Net Weight (kgs) ENVIRONMENT Humidity Noise Level MANAGEMENT	7.9	8.5 0-90 % RH @ 0- 40' Less th	410 x s 11.8 °C (non-condensing) an 40dB	13.1
Dimension, D x W x H (mm) Net Weight (kgs) ENVIRONMENT Humidity Noise Level MANAGEMENT USB Port	7.9	8.5 0-90 % RH @ 0- 40' Less th	410 x s 11.8 °C (non-condensing) an 40dB	13.1
Dimension, D x W x H (mm) Net Weight (kgs) ENVIRONMENT Humidity Noise Level MANAGEMENT USB Port NEXT PARTNUMBERS	7.9	8.5 0-90 % RH @ 0- 40' Less th	410 x s 11.8 °C (non-condensing) an 40dB	13.1
Dimension, D x W x H (mm) Net Weight (kgs) ENVIRONMENT Humidity Noise Level MANAGEMENT USB Port NEXT PARTNUMBERS PRODUCT PARTNR.	7.9 Supports W	8.5 0-90 % RH @ 0- 40' Less the /indows® 2000/2003/XP/Vista/2	410 x s 11.8 °C (non-condensing) an 40dB	13.1

Product specifications are subject to change without further notice