

Dell UltraSharp U2722DE (DELL-U2722DE)

Dell UltraSharp U2722DE - LED monitor - 27" - 2560 x 1440 QHD @ 60 Hz - IPS - 350 cd/m² - 1000:1 - 5 ms - HDMI, DisplayPort, USB-C - with 3 years Advanced Exchange Service - for Latitude 5320, 5520; OptiPlex 3090; Precision 7560; XPS 13 9310, 15 9510



Elevate your productivity on this innovative monitor that delivers true-to-life color and seamless connectivity.

Key Selling Points

Connected productivity. Vibrant color. Take your work to new heights with this 27-inch QHD monitor featuring outstanding connectivity, brilliant color coverage including DCI-P3, ComfortView Plus - an always on built-in low blue light screen - and USB-C port with

Product Features

Designed with wellness in mind

Optimize eye comfort with ComfortView Plus - an always on, built-in low blue light screen that reduces blue light emissions while delivering excellent color.

In-Plane Switching technology

See consistent color and picture quality across a wide 178° / 178° viewing angle.

Seamless view

Expand your view with virtually borderless InfinityEdge. With a four-sided, ultrathin bezel, you can work with a clear, edge-to-edge display. Use the daisy-chain feature for a seamless multimonitor setup.

Connect to productivity

With RJ-45 and USB-C, your monitor serves as a productivity hub that delivers stable Ethernet and power.

Quick-access front ports

Quick-access USB-C and SuperSpeed USB ports located at the front of the monitor enable fast connections to peripherals and mobile device charging.

Moves with you

Adjust to your comfort with tilt, swivel, pivot and height adjustments for optimal viewing comfort.

Main Specifications

Product Description	Dell UltraSharp U2722DE - LED monitor - QHD - 27"
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class E
Power Consumption (On mode)	20.4 W
Features	USB 3.2 Gen 2/USB-C hub, USB PD 90 Watt
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.2331 mm
Brightness	350 cd/m ²
Contrast Ratio	1000:1
Response Time	5 ms (fast), 8 ms (normal)
Colour Support	1.07 billion colours
Colour Gamut	100% Rec 709, 100% sRGB, 95% DCI-P3
Input Connectors	HDMI, DisplayPort, USB-C
Built-in Ethernet	Yes

Display Position Adjustments	Height,pivot (rotation),swivel,tilt
Screen Coating	Anti-glare,3H Hard Coating
Voltage	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH) - with stand	61.134 cm x 18.5 cm x 38.513 cm
Environmental Standards	TCO Certified Displays 8,TCO Certified Edge Displays,ENERGY STAR Qualified
Compliant Standards	Plug and Play,RoHS,NFPA 99,TUV Rheinland,BFR-free,DisplayPort 1.4,HDCP 1.4,PVC-free
Bundled Services	3 years Advanced Exchange Service
Designed For	Latitude 5320,5520;OptiPlex 3090;Precision 7560;XPS 13 9310,15 9510

Extended Specification

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class E
Diagonal Size	27"
Built-in Devices	USB 3.2 Gen 2/USB-C hub
USB Power Delivery	90 Watt
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	QHD 2560 x 1440 at 60 Hz
Pixel Pitch	0.2331 mm
Pixel Per Inch	108.78
Brightness	350 cd/m ²
Contrast Ratio	1000:1
Colour Support	1.07 billion colours
Colour Gamut	100% Rec 709,100% sRGB,95% DCI-P3
Response Time	5 ms (fast),8 ms (normal)
Vertical Refresh Rate	49 - 76 Hz
Horizontal Refresh Rate	30 - 90 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare,3H Hard Coating
Backlight Technology	LED backlight
Features	Picture by picture,OSD lock,integrated cable management,Flicker Free technology,Mercury free,arsenic-free glass,Dell Easy Arrange,Low Blue Light technology,Delta E<2 calibration
Dimensions (WxDxH)	61.134 cm x 18.5 cm x 38.513 cm - with stand

Connectivity

Interfaces	HDMI
	DisplayPort 1.4 (HDCP 1.4)
	DisplayPort output
	USB-C 3.2 Gen 2 upstream
	USB-C 3.2 Gen 2 downstream (power up to 15W)
	3 x USB 3.2 Gen 2 downstream
	USB 3.2 Gen 2 downstream with Battery Charging 1.2

Audio line-out (mini-jack)
USB-C 3.2 Gen 2 upstream/DisplayPort 1.4 Alt Mode (power up to 90W)
Network (RJ-45)

Mechanical

Display Position Adjustments	Height,pivot (rotation),swivel,tilt
Tilt Angle	-5/+21
Swivel Angle	90
Rotation Angle	180
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm

Miscellaneous

Features	Security lock slot (cable lock sold separately)
Cables Included	1 x DisplayPort cable - DisplayPort to DisplayPort - 1.8 m 1 x SuperSpeed USB cable - USB Type C to A - 1 m 1 x USB-C to USB-C cable - 1 m
Compliant Standards	Plug and Play,RoHS,NFPA 99,TUV Rheinland,BFR-free,DisplayPort 1.4, HDCP 1.4,PVC-free
Security Slot Type	Kensington security slot

Power

Input Voltage	AC 120/230 V (50/60 Hz)
Power Consumption (On mode)	20.4 W
Power Consumption SDR (On mode)	20.4 kWh/1000h
Power Consumption (Typical)	20.4 Watt
Power Consumption (Max)	197 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption (Off Mode)	0.3 Watt

Dimensions &Weight

Dimensions &Weight Details	With stand - width:61.134 cm - depth:18.5 cm - height:38.513 cm Without stand - width:61.134 cm - depth:4.95 cm - height:35.201 cm - weight:4.78 kg
----------------------------	--

Dimensions &Weight (Shipping)

Shipping Weight	10.01 kg
-----------------	----------

Environmental Standards

TCO Certified	TCO Certified Displays 8,TCO Certified Edge Displays
ENERGY STAR Certified	Yes

Manufacturer Warranty

Bundled Services	3 years Advanced Exchange Service
------------------	-----------------------------------

Environmental Parameters

Min Operating Temperature	0 °C
---------------------------	------

Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)

Compatibility Information

Designed For	Dell Latitude 5320,5520 Dell OptiPlex 3090 Dell Precision 7560 Dell XPS 13 9310,15 9510
--------------	--

What's in the box

Dell UltraSharp U2722DE
DisplayPort cable - 1.8 m
SuperSpeed USB cable - 1 m
USB-C to USB-C cable - 1 m

*TD SYNEX is not responsible for errors in the documentation of products.