Technical Specifications

HP P34hc G4 WQHD USB-C Curved Monitor



Front

1. Power LED



Technical Specifications

HP P34hc G4 WQHD USB-C Curved Monitor



Back

- 1. OSD Buttons
- 2. Power Button
- 3. Power Connector
- 4. HDMI Port
- 5. DisplayPort[™]

- 6. USB Type-C[™]
- 7. USB-B
- 8. USB-A x4
- 9. Audio Port
- **10.** Security Cable Slot



Technical Specifications

Models: 21Y56AA/21Y56AT/21Y56AS

Panel Specifications	Display Size (Diagonal)	34"
Fallet Specifications	Panel Technology	VA
	Curved Panel	Yes
	Refresh Rate	48-100 Hz
		8 bit
	Panel Bit Depth Aspect Ratio	21:9
	Brightness (Typical)	250 nits
	Contrast Ratio (Static)	3,500:1
	Dynamic Contrast Ratio	•
	Flicker Free	5,000,000:1 Yes
	Pixel Pitch	0.07725 * 0.23175 mm
	Pixels Per Inch (PPI)	110 PPI
	Backlight Lamp Life Minimum (To Half	30,000k
		50,000K
	Brightness - In Hours)	Edge lit
	Backlight Type	Edge-lit
	Screen Treatment	Anti-glare
	Hardness	3H
	Haze	AG25%
	Response Time (Typical)	5ms GtG (with overdrive)
	Horizontal Viewing Angle (Typical	178°
	Cr>10)	1700
	Vertical Viewing Angle (Typical Cr>10)	178°
	Panel Active Area (W X H)	797.22 (H) x333.72 (V) mm
	Manufacturers; Actual Performance May Vary E	he Typical Specifications Provided By HP's Component
	Manufacturers, Actual Performance May vary E	inter higher of Lower.
Color	NTSC	85%
20101		05%
Color Management	Color Space/ Subsampling Support	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2
	Color Space/ Subsampling Support RGB Channel Adjust	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain
	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K
	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature)
	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K,
	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K,
	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K,
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K
	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21°
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready Detachable Stand	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot Yes
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready Detachable Stand Warranty	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot Yes 3 years
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready Detachable Stand Warranty Low Blue Light	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot Yes 3 years Yes (TÜV certified)
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready Detachable Stand Warranty Low Blue Light Speaker Output Power	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot Yes 3 years Yes (TÜV certified) 2 x 3W
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready Detachable Stand Warranty Low Blue Light Speaker Output Power Display Software	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot Yes 3 years Yes (TÜV certified) 2 x 3W HP Display Center
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready Detachable Stand Warranty Low Blue Light Speaker Output Power	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot Yes 3 years Yes (TÜV certified) 2 x 3W HP Display Center Brightness+, Color, Image, Input, Power, Menu,
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready Detachable Stand Warranty Low Blue Light Speaker Output Power Display Software On Screen User Controls	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot Yes 3 years Yes (TÜV certified) 2 x 3W HP Display Center Brightness+, Color, Image, Input, Power, Menu, Management, Information, Exit
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready Detachable Stand Warranty Low Blue Light Speaker Output Power Display Software On Screen User Controls	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot Yes 3 years Yes (TÜV certified) 2 x 3W HP Display Center Brightness+, Color, Image, Input, Power, Menu, Management, Information, Exit WQHD (3440 x 1440)
Color Management	Color Space/ Subsampling Support RGB Channel Adjust Default Color Temperature Factory Color Calibrated Factory Color Presets Bezel Color Tilt Height Adjust Range VESA Mounting Security Lock Ready Detachable Stand Warranty Low Blue Light Speaker Output Power Display Software On Screen User Controls	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 Yes, Gain 6500K Yes (Color Temperature) Warm - 5000K, Neutral - 6500K, Cool - 9300K 3-sided Micro Edge Black Head -5 to +21° 100mm 100 mm x 100 mm Standard Security Lock Slot Yes 3 years Yes (TÜV certified) 2 x 3W HP Display Center Brightness+, Color, Image, Input, Power, Menu, Management, Information, Exit



Technical Specifications

	Preset Graphic Modes/Supported	640 × 480 @ 59.940Hz
	Resolutions	800 × 600 @ 60.317Hz
		1024 × 768 @ 60.004Hz
		1280 × 720 @ 60Hz
		1280 × 800 @ 59.810Hz
		1280 × 1024 @ 60.020Hz
		1440 × 900 @ 59.887Hz
		1600 × 900 @ 60Hz
		1680 × 1050 @ 59.954Hz
		1920 × 1080 @ 60Hz
		1920 × 1200@ 59.95Hz
		3440 × 1440@ 59.973Hz
		3440 × 440@ 99.982Hz
	Minimum Vertical Scan Rate	48 Hz
	Maximum Vertical Scan Rate	100 Hz
	Minimum Horizontal Scan Rate	30.0 kHz
	Maximum Horizontal Scan Rate	160.0 kHz
	Maximum Pixel Clock	550.0 MHz
	User-Assignable Function Buttons	Yes, 3 (8 options)
	Audio	Built-in speakers
	Languages	10 (English, Spanish, German, French, Italian, Netherlands,
	Languages	Portuguese, Japanese, T-Chinese and S-Chinese)
		rorruguese, supurese, r chinese and s chinese,
Connector Types	DisplayPort™	1 DisplayPort™ 1.2
	HDMI	1 HDMI 2.0
	HDCP	Yes, DisplayPort [™] and HDMI and USB-C
	USB Type-C™ Video Input	1 USB Type-C [™] (Power delivery up to 65W)
	USB- A	4 USB-A 3.2 Gen 1
	USB-B (Hub enablement)	1 USB-B
	Audio Port	1 Line Output
Special Features	User Presets	Yes
Power & Operating	Power Supply	Internal
Specs	Power Source	100–240 VAC 50/60 Hz
•	Power Consumption- Max	190W
	Energy Saving/Stand By Mode	0.5W
	Power Consumption- Typical	48W
ENERGY STAR Data	Operational Mode at 100 VAC	34W
	Operational Mode at 115 VAC	34W
	Operational Mode at 230 VAC	34W
Operating Conditions	Operating Temperature - Celsius	5° - 35°C
	Operating Temperature - Fahrenheit	41° - 95°F
	Non-Operating Temperature - Celsius	-20° - 60°C
	Non-Operating Temperature -	-4° - 140°F
	Fahrenheit	
	Operating Humidity	20% - 80% (non-condensing)
	Non-Operating Humidity	5% - 95%
	Operating Altitude	0 - 5,000 m (16,400 ft.)
	Non-operating Altitude	0 - 12.192 m (40,000 ft.)
EU Energy Efficiency Class (ERP Lot5)	On-mode Power Consumption	32W



Technical Specifications

	Energy Efficiency Class	t G	
Environmental Features and Certifications	Mercury-free LED display backlighting Arsenic-Free Display Glass Low Halogen	Yes Yes Yes WW application	
	Agency Approvals And Certifications	CE,CB,KC/KCC/KES/ICE/ISO EAC/cTUVus/CCC/CEL/VCCI/	
	Microsoft WHQL Certification	Yes	
	ENERGY STAR [®] Certified	Yes	
	EPEAT® Registered Regions need to verify by country	CEL Grade 1	
	China Energy Label	Yes	
	TCO Certified Edge	Yes	
	TCO Certified	Yes	
	SmartWay Transport Partnership	Yes (NA Only)	
Contains Recycled Plastics	Contains Recycled Plastics	85%	
Unit Product/Package Specifications	Product Dimensions (Unpacked with stand) (W x D x H)	80.94 x 23.49 x 51.80 cm	31.89 x 9.25 x 20.40 in
	Product Dimensions (Packed) (W x D x H)	95 x 22.5 x 48 cm	37.4 x 8.86 x 18.9 in
	Display Head Dimensions (Unpacked without stand) (W x D x H)	80.94 x 11.21 x 36.69 cm	31.89 x 4.41 x 14.44 in
	Base Area Footprint	166.88 x 228.9 mm	6.57 x 9 in
	(w x d mm) Bezel Measurements - Metric Product Weight	Top19.22mm Side 14.35mm Bottom19.25mm 10.51kg	Top 0.76 in Side 0.57 in Bottom 0.76 in 23.17lb
	(Unpacked with stand) Product Weight (Packed)	16.7kg	36.8lb
	Product Weight (Head Only)	7.85kg	17.31lb
What's in the box?	AC power cord (1.83m) 6.0 ft USB C-C cable (1.8m) 5.9 ft DP cable (1.8m) 5.9ft HDMI cable (1.8m) 5.9ft QSP Warranty card		
User Guide and Warranty Languages	User Guide Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish	
	Warranty Languages	Japanese, Kazakh, Korean,	T. Chinese, Czech, Danish, man, Greek, Hungarian, Italian, Norwegian, Polish, Brazilian enian, Spanish, Swedish and



Technical Specifications

Copyright © 2021 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.



Summary

Change Log				
January 28, 2021	V1 to V2		Techspecs updated	
March 10, 2021	V2 to V3	Added	Energy Efficiency Class	
April 13, 2021	V3 to V4	Removed	KVM and PbP features	
February 8, 2023	V4 to V5	Updated	Energy Efficiency Class section	
April 13, 2023	V5 to V6	Updated	Color Management section	
	V6 to V7			