### SNOM

# A190

Wireless multicell DECT Headset







Superior wideband sound



Lightweight design

#### **Benefits**

- $\cdot$  Superior wideband sound
- $\cdot$  Noise reduction
- $\cdot$  Echo cancellation
- $\cdot$  Stand-alone and paired mode
- $\cdot$  Lightweight design
- $\cdot$  Handover and roaming in multi cell setup

## snom

#### Headset

- Over-the-head wearing style with adjustable microphone boom
- Monoaural headset with audio controls and LED indicator
- Stand-alone mode: an account is configured to an A190
- Paired mode: an account is shared by the A190 and a DECT-handset
- $\cdot$  Wideband audio support
- · Talk-time 7h (NB), 6h (WB)
- · Light-weight design 45g
- · HAC compliant
- $\cdot$  Compatible to M-series base station  $^{\scriptscriptstyle (1)}$

#### Battery

- · Type: lithium-ion, 320mAh built-in
- · Talktime WB: 6h
- · Talktime NB: 7h
- · Stand-by-time: 100h
- Battery charge time 0-100%: < 4h

#### Charger

- · Input: 5V DC, 350mA
- Integrated weight and rubber feet for solid desktop setup

#### Power adapter

- · Input: 100-240V AC, 50/60Hz, 150mA
- · Output: 5V DC, 350mA
- Plug: interchangeable clips, EU and US clips included
- $\cdot$  Charging conditions: +5° C to 45° C

#### Range

- $\cdot$  Indoors: up to 50m
- $\cdot$  Outdoors: up to 300m



#### On the internet

https://www.snom.com/a190/

#### Version 1.0.0 / en / 10 · 2019

Copyright 2019 Snom Technology GmbH. All rights reserved. Snom is a registered trademark of Snom Technology GmbH and its affiliates in the European Union, USA, Japan, China and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, are legally protected trademarks of Snom Technology GmbH. Other mentioned trademarks or registered trademarks are the property of their respective manufacturers or owners. Product specifications are subject to change without notice. We do not accept liability for printing errors and mistakes. snom.com

#### DECT

- $\cdot$  Frequency band:
  - 1,880–1,900Mhz (EU)
  - 1,920–1,930Mhz (US)
- $\cdot$  Output power: EU<250mW, US<100mW
- · Protocols: DECT, DECT 6.0
- Wideband voice
- · DECT encyption
- · DECT band auto-sensing

#### User interface

- · Voice prompts (English)
- $\cdot$  Volume, mute control
- $\cdot$  AUX key
- $\cdot$  Call control key
- $\cdot$  LED status indication

#### Installation

- $\cdot$  Easy registration to compatible base stations  $^{(1)}$
- · Software update: over-the-air via the base station

#### Marking

- · CE
- · IEC 60950

### Part Number: 00004444

#### <sup>(1)</sup> Compatible base stations

- Snom M900 PN 00004426 (EU version)
- PN 00004441 (US version)
  Snom M700 PN 00003928 (EU version)
  - PN 00003929 (US version)
- Snom M300 PN 00003986 (EU version)
  - PN 00003985 (US version)