

M400



Dual-cell scalability



Power over Ethernet (PoE)



Security (TLS & SRTP)



OTA Updates



Directory

The M400 dual-cell DECT base station for seamless business mobility

The dual-cell M400 DECT base station offers the full range of telephony business features. In a dual cell installation, it ensures uninterrupted availability, seamless handover and can be used with all Snom multicell endpoints. The M400 provides an automated dual-cell chain to the local network to upscale the communication solution and features a powerful DECT call manager for up to 20 parallel

calls in a dual-cell installation with up to 40 SIP accounts in a dual-cell setup. For Cloud and VoIP PBX partners, the M400 offers remote maintainability and zero-touch deployment. The M400 complies with the latest encryption standards and shares the same architecture as the M900 multicell system for the latest software and security updates.

Technical Specifications

Basics

- Colour white
- Wall mountable
- Product numbers
 - M400 | DECT dual-cell base station | EU & UK | PN 00004587
 - M400 | DECT dual-cell base station | Americas | PN 00004588

Dimensions and weight

- Dimensions (H x W x D, approx.)
 - 112 mm x 90 mm x 36 mm
- Weight (approx.)
 - 170 g

Indicators and keys

- 1 multicolour LED
- 1 dedicated function key Reset

Audio codecs and features

- Audio codecs
 - G.711 (A-law, μ -law), G.722, G.726, G.729
- Related features
 - Codec negotiation, codec switching

Interfaces and connections

- M400 power options
 - Power over Ethernet (PoE), IEEE 802.3af, class 2
- Wired interfaces
 - RJ45-8P8C 10/100 Mbit Ethernet port
- Wireless interfaces
 - DECT

User interfaces and setup

- Configuration and setup via menu-driven web user interface (WUI)
- Automatic configuration via provisioning
 - Loading of settings and firmware via HTTP / HTTPS / TFTP
 - Secure provisioning with preinstalled certificate
 - Cloud Zero-Touch Provisioning
- Localization
 - Timezone, Dial tone
- Diagnostic
 - DECT messages, alarms, location
- Related features
 - XML browser
 - Automatic dual-cell chain setup
 - Compatible handset feature RSSI tool, no additional measurement equipment needed

Directory support and call features

- Directory support
 - LDAP (server-based directory)
 - XML phonebook support
- Related features
 - List of registered mobile handsets, repeaters, location gateways

DECT technology and features

- Standard: DECT¹
 - Antenna diversity (2 internal omni-directional antennas for better transmission and reception)
 - Authentication/encryption of base and handset
 - Seamless handover and roaming using DECT synchronisation
 - Wideband audio
- Frequency band
 - Europe: 1,880 - 1,900 MHz
 - USA: 1,920 - 1,930 MHz
- Output power
 - Europe: less than 250 mW
 - USA: less than 100 mW
 - Level (dbm): 14, 17, 20, 24
- Coverage
 - Up to 50 m indoor range / 300 m outdoor range
- Handsets
 - Up to 20 per base station / 40 per dual-cell installation
- Repeaters
 - Up to 6 per base station / 12 per dual-cell installation
- Calls in single-cell system
 - Up to 10 narrowband calls / 5 wideband calls
- Calls in dual-cell system
 - Up to 20 narrowband calls / 10 wideband calls
- Related features
 - Software upgrade over the air (SUOTA)

Networking technologies and protocols

- Network technologies
 - VLAN (IEEE 802.1Q)
- Secure VoIP protocols
 - SIPS (SIP over TLS), SRTP (RFC 3711)
- Network protocols
 - DHCP, NTP, LLDP-MED, HTTP
- Secure network protocols
 - TLS V1.2, HTTPS
- Quality of Service (QoS)
 - ToS

Technical Specifications

Interoperability

- Certified VoIP partner

Environmental conditions

- Operating ambient temperature: -10 °C to 50 °C (14 °F to 122 °F)

Package contents

- DECT base station unit
- Quick Installation Guide (QIG)
- Information sheets (security, standards)

¹ DECT devices manufactured for the United States and Canada are marketed as DECT 6.0

Type approval and standards conformance

- Information technology equipment - Safety 62368-1
- WEEE 2012/19/EU
- FCC (ID T7HX9431)

Accessories

- 00004607 | [M30](#) | DECT handset | EU & UK
- 00004423 | [M70](#) | DECT handset
- 00004424 | [M80](#) | DECT handset
- 00004189 | [M85](#) | DECT handset
- 00004425 | [M90](#) | DECT handset

Series overview



M30



M70



M80



M85



M90



M400



M900



M900 outdoor



Disclaimer

For further product information visit: [Snom website](#) | [Snom Service Hub](#) | [Warranty information](#)

© 2022 Snom Technology GmbH. All rights reserved.

Snom is a registered trademark of Snom Technology GmbH in the European Union, USA, Japan, China and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, are legally protected trademarks of Snom Technology GmbH. Other mentioned trademarks or registered trademarks are the property of their respective manufacturers or owners. Product specifications are subject to change without notice. We do not accept liability for printing errors and mistakes.